

UT32

8" Rugged Android Tablet

The UT32 is an 8-inch tablet with Full HD resolution (1280 x 800 pixels). The screen is also bright and colorful, making it easier for you to work. As far as internal performance goes, this is an excellently fast tablet; you can expect plenty of speed and fewer frozen apps thanks to the tablet's 2.2GHz octa-core processor. Thanks to its impressive 8200 mAh rechargeable battery, the device can operate for 6 hours on a single charge. The UT32 is a superb rugged tablet option for anyone looking for portable, easy-to-use tablets.



Resistive Touchscreen

Enjoy a projected capacitive touchscreen that is a more scratch-resistant glass substrate for industrial automation or other harsh working environmental conditions.

Good Compatibility with Android System

Get all the apps and services you need from the Google Play Store, just like your own cellphone.

IP67 Rated and MIL-STD-810G Certified

No longer need to worry about concrete dust, water, oil, and other substances that could otherwise damage the device, for the UT32 is a completely sealed tablet, has no fear of dirt, vibrations, cold, and heat.



Website



Social media

Product Specification

UT32

8" Rugged Android Tablet



System	
Processor	Qualcomm MSM8953 Pro Octane-Core 2.2 GHz
OS	Android 10.0
Memory	4 GB
ROM	64 GB

Screen	
Screen size	8"
Resolution	1280 x 800
Density	320 dpi
Brightness	400 nits
Touch panel	Capacitive

Camera	
Rear	13 MP
Front	5 MP
Flash light	Support
Auto focus	Support

Power Supply	
Battery	Rechargeable and replaceable Lithium-ion battery 3.8 V, 8200 mAh
Working time	15 hours
Charging time	≤ 7 hours
Speaker	Support
Microphone	Support
Light	Support
Proximity	Support
Magnetometer	Support
Gyroscope	Support
Accelerometer	Support
Gravity	Support
Compass	Support
Barometer	Support

GNSS	
Tracking	GPS, BDS, GLONASS, GALILEO
Accuracy	Single: 1 – 3m

Communication	
GSM	■ GSM, WCDMA, LTE ■ Nano SIM x 1
Wi-Fi	802.11 a/b/g/n/ac (2.4 & 5GHz)
Bluetooth	V4.2
SD card	Up to 128 GB
USB	■ USB Type-C x 1

Physical	
Dimension	242 mm x 152 mm x 17.8 mm
Weight	With battery 660g
	Without battery 505g
Operating temperature	-20 C - +60 C
Storage temperature	-40 C - +70 C
Water/dust proof	IP 67
Shock	Survive a 1.2 m drop on concrete floor
Humidity	0-95% RH, non-condensing
Buttons	■ Menu x 1 ■ Home x 1 ■ Return x 1 ■ Volume (+/-) x 2 ■ Power x 1 ■ FN x 2
Certificate	FCC, IC, CE, ROHS, REACH, WEEE