Product data sheet

Power tools for trade & industry



Line Laser

GLL 3-80 Professional



GBP 393.54*

* Price including VAT

3 x 360° for visibility on a new level

Part number: 0 601 063 S00

> More product information

Technical Data

webshop-pdp-section-technical-data-table-key-Technical data

recillical data	
Laser diode	Line: 630 - 650 nm, < 10mW
Operating temperature	-10 - 40 °C
Storage temperature	-20 - 70 °C
Laser class	2
Working range	30 m
Working range with receiver	120 m
Working range without receiver	30 m
Accuracy	± 0.2 mm/m
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 54
Operating time (max.)	4 h in 3-line mode
Tripod thread	1/4", 5/8"
Colour of laser line	red
Projection	3 x 360° line
Compatible laser receivers	LR 6 + 7

webshop-pdp-section-technical-data-table-key-Battery and power

Power supply	4 x 1.5 V LR6 (AA)
--------------	--------------------

webshop-pdp-section-technical-data-table-key-Size and weight

0.82 kg Weight, approx.

BOSCH Invented for life

Product data sheet

Power tools for trade & industry

Advantages

- High visual clarity is provided by high-powered diodes
- 3 x 360° lines allow for simultaneous horizontal and vertical levelling applications for highly efficient work
- Intuitive user interface offers easy operation















